

MATERIAL SAFETY DATA SHEET

MANUFACTURER: Texas Cement Products, Inc.
4000 Pinemont Drive
Houston, Texas 77018
Emergency Phone: 713-692-8411

SECTION I: PRODUCT IDENTIFICATION

IDENTITY: Nu-Deck Color Stain

SECTION II: COMPONENTS

	<u>CAS Reg. No</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Acrylic Polymer dispersed in water		Non Hazardous	
Limestone	1317-65-3	5	10 mg/m ³ respirable
Titanium Dioxide	13463-67-7	10	10 mg/m ³ respirable
2-Butoxy ethanol	000111-76-2	25 PPM	25 PPM skin
Ammonium Hydroxide	1335-21-6	50 PPM	25 PPM

SECTION III: PHYSICAL PROPERTY INFORMATION

Boiling Point:	212 - 400 °F
Vapor Pressure (mm Hg):	Greater than 1
Vapor Density:	Heavier than air
Specific Gravity (water=1):	1.1- 1.4
Solubility in Water:	Dilutable
Evaporation rate	(BU'TYL ACETATE -1): Less than one
Appearance / Odor-	Thick white to colored, textured mixture, mild ammonia odor, pH 8-10

SECTION IV: FIRE AND EXPLOSION HAZRD INFORMATION

Flash Point	>199 F PMCC
Explosion Limits:	N/A
Extinguishing Media:	Carbon Dioxide, Dry Chemical, Alcohol Foam
Unusual Fire and Explosion Hazards:	Closed containers may explode due to the build-up of pressure when exposed to extreme heat.
Special Fire Fighting Procedures:	Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure buildup.

SECTION V: REACTIVITY DATA

STABILITY- Stable

INCOMPATIBILITY- None Known

HARRDOUS DECOMPOSITION PRODUCTS- By fire: Carbon Dioxide, Carbon Monoxide

HARRDOUS POLYMERIZATION- Will Not Occur

Date Prepared: March 20, 2007

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

Routes of Exposure: INHALATION - YES EYES/SKIN – YES

ACUTE Health Hazards: Irritation of eyes, skin and upper respiratory system. In a confined area, vapors in high concentration may cause headache, nausea or dizziness.

Signs and Symptoms of Overexposure: Redness and itching or burning sensation may indicate eye or excessive skin exposure.

Emergency and First Aid Procedures:

IF INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

IF SWALLOWED: Get medical attention.

SECTION VII SPILL OR LEAK PROCEDURES:

Steps to be taken in case material is released or spilled: Do not allow material to flow into sewers and open bodies of water.

Ventilate and remove with inert absorbent.

Disposal Method: Waste from Latex Finishes is not hazardous.

Incinerate in approved facility. Do not incinerate closed container.

Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

SECTION VIII: PROTECTION INFORMATION

Precautions To Be Taken During Use: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

Ventilation: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits.

Respiratory Protection: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II. When sanding or abrading the dried film, wear a dust mist respirator approved by NIOSH/MSHA for dust which may be generated.

Protective Gloves: Rubber

EYE Protection: Wear safety spectacles with side shields.

Precautions To Be Taken In Handling And Storing: Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.