SAFETY DATA SHEET



Texrite Multi-purpose

· · · ·	-	As of date:	2018
Section 1	Product Description		
Product Name: Recommended Use: Synonyms:	Multi-purpose Ceramic tile and stone tile adhesive Latex –Polymer Thinset, Dry-set mortar, Bondcoat, Polymer modified m	ortar	
Manufacturer:	Texas Cement Products, dba Texrite 4000 Pinemont, Houston, Texas 77018, USA 713-682-8411 www.texrite.com		
General Phone Number: General Fax Number:	713-682-8411 (8am-3pm, CST, M-F) 713-688-2488		

Section 2 Hazards Identification

Classification of the chemical in accordance with paragraph (d) of 1910.1200;

Signal Word:	Danger
GHS Class:	Serious Eye Damage/Eye Irritation, Category 1, Skin Corrosion/Irritation, Category 2 Skin Sensitizer/Allergic skin reaction, Category 1 Carcinogen/May cause cancer if inhaled, Category 1A, May cause respiratory irritation, STOT SE3 Damage to organs through prolonged or repeated exposure if inhaled, STOT RE1
Hazard Statements:	H100s = General, H200s = Physical, H300s = Health, H400s = Environmental
	 H315 -Causes skin irritation. H317 -May cause an allergic skin reaction. H318 -Causes serious eye damage. H335 -May cause cancer if inhaled. H350.A -May muse respiratory irritation. H372.A - Causes damage to organs through prolonged or repealed exposure if inhaled.
	 P201 -Obtain special instructions before use. P202 -Do not handle until all safety precautions have been read and understood. P260.B -Do not breathe dust. P264.3 -Wash skin thoroughly after handling. P270 -Do not eat, drink or smoke when using this product. P271 -Use only outdoors or in a well-ventilated area. P272 -Contaminated work clothing should not be allowed out of the workplace P280.B -Wear protective gloves and eye, face protection. P302+P3529, -IF ON SKIN. Wash with plenty of water.
Precautionary Statement	 S: P201 -Obtain special instructions before use. P202 -Do not handle until all safety precautions have been read and understood. P260.B -Do not breathe dust. P264.3 -Wash skin thoroughly after handling.

P270 -Do not eat, drink or smoke when using this product. P271 -Use only outdoors or in a well-ventilated area. P272 -Contaminated work clothing should not be allowed out of the workplace P280.B -Wear protective gloves and eye, face protection. P302+P3529, -IF ON SKIN. Wash with plenty of water P304+P340 -IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 -IF exposed or concerned: Gel medical advice / attention. P310.A -Immediately call a POISON CENTER. P314 -Get medical advice/attention if you feel unwell. P321 .A -Specific treatment (see supplementary instructions on this label) P333+P313 -If skin irritation or rash occurs: Get medical advice/attention. P362+P364 -Take & contaminated clothing and wash it before reuse. P403+P233 -Store in a well-ventilated place. Keep container lightly dosed. P405 -Store locked up. P501A -Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations. Ingredients(s) with unknown acute toxicity: None

o ()

Hazards not otherwise classified identified during the classification process: None

Section 3 Composition Information and Ingredients

Mixture:

Component Name Silica Sand Portland Cement	<u>CAS #</u> 14808-60-7 65997-15-1	<u>WT %</u> 40-80%, 20-45%	Classification Carc. 1A, H350A, STOT RE 1, H372A STOT SE 3, H335: Eye Dam 1,H318 Skin Sens. 1, H317; Skin Irrit. 2, H315
Calcium sulfate	7778-18 -9	1-5%	H317; Skin Irrit. 2, H315 STOT SE 3, H335:

Section 4 First-Aid Measures

Emergency and First Aid Procedures

Inhalation:	Remove casualty to fresh air and keep at rest. If breathing is irregular or stopped, administer artificial respiration. In case of inhalation, consult a doctor immediately and show him packing or label.		
Eyes:	IF IN EYES: Rinse cautiously with water with the eyelids open for a sufficient length of time. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation continues, then get medical advice/attention immediately. Protect uninjured eye.		
Skin Contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Ingestion:	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.		
Most Important symptoms/effects, acute and delayed: Eye Irritation Eye damages Skin Irritation Erythema Indication of any immediate medical attention and special treatment needed: In case of accident or unwellness, seek medical advice immediately (show directions for use or			
	safety data sheet if possible).		
Section 5	Fire Fighting Measures		

Extinguishing Media: Fire Fighting Methods and Protection:	Use carbon dioxide, or water spray when fighting fires involving this material. Firefighters should wear full protective equipment and NIOSH approved self- contained breathing apparatus.
Fire and/or Explosion Hazards:	Do not inhale explosion and combustion gases. Burning produces heavy smoke.
Hazardous Combustion Products:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.
Special protective equipment and precau	utions for fire-fighters:
	Use suitable breathing apparatus.
	Collected contaminated fire extinguishing water separately. This must not be discharged into drains.
	Move undamaged containers from immediate hazard area if it can be done safely.

Section 6	Accidental Release Measures		
Steps to Take in Case N	laterial Is	Wear personal protection equipment. Wear breathing apparatus if exposed to vapors/dusts/aerosols. Provide adequate ventilation. Use appropriate respiratory protection. See protective measures under section 7 and 8. Ventilate	
Released or Spilled:		the contaminated area. Suitable material for taking up: absorbing material, organic, sand. Wash with plenty of water.	
Section 7	Handling and	Storage	
Handling:		Avoid contact with skin and eyes, Inhalation of vapors and mists. Exercise the greatest care when handling or opening the container. Use localized ventilation system. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Contaminated clothing should be changed before entering eating areas. Do not eat or drink while working. See also section 8 for recommended protective equipment. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face	
Storage:		protection. Keep dry. Keep container tightly closed & upright when not in use to prevent leakage.	

Storage Code:

N.A.

Section 8	Expos	ure Cont	rols / Person	al Protectio	on			
List of compone	ents with OEL valu	е						
<u>Component</u>	OEL Type Country	<u>Ceiling</u>	Long Term <u>mg/m3</u>	Long Term ppm	Short Term mg/m3	Short Term ppm	<u>Behavior</u>	Note
Silica Sand	ACGIH		0.025					A2-SupsectedHuman Carcinogen; lung cancer; pulmonary fibrosis
Portland cement	OSHA OSHA ACGIH		15 5.0 1					A4- Not classifiable as a Human Carcinogen;: pulmonary function: respiratory symptoms;
Calcium sulfate	OSHA OSHA ACGIH		15 5 10					asthma nasal symptoms
Control Parameters Engineering Measures:			General roon under normal		U 1			erator comfort dust

Personal Protective Equipment (PPE):

Respiratory Protection: Respirator Type(s): Eye Protection: Skin Protection: No respiratory protection required under normal conditions of use. Use NIOSH approved air purifying respirator with dust filter. Wear close fitting safety glasses or goggles when handling this product. Avoid skin contact by wearing clothing that provides comprehensive protection. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. PVC, neoprene, rubber, ntrile

Gloves:

Section 9 Physical and Chemical Properties

Appearance:	Solid, Gray or White Powder
Odor:	Cement likes
Odor Threshold:	None
pH (Neutrality):	N.A.
Melting Point/Freezing Point:	N.A.
Boiling Range (Ibp,50%,Dry Point):	N.A.
Flash Point (Test Method):	N.A.
Evaporation Rate	
(n-Butyl Acetate=1):	N.A.
Flammability Classification:	N.A.
Lower Flammable	
Limit in Air (% by vol):	N.A.
Upper Flammable	
Limit in Air (% by vol):	N.A.
Vapor Pressure (mm of Hg)@20 C:	N.A.
VAPOR DENSITY (Air=1):	N.A.
GRAVITY @ 68/68F / 20/20C:	
Specific Gravity (Water=1):	N.A.
Pounds/Gallon:	N.A.
Water Solubility:	Soluble
Partition Coefficient (n-Octane/Water):	N.A.
Auto Ignition Temperature:	N.A.
Decomposition Temperature:	N.A.
Decomposition remperature.	Ν.Α.
Other Information	
Substance Groups relevant properties	N.A.
Miscibility:	N.A.
2	N.A.
Fat Solubility:	N.A.
Conductivity:	IN.A.

Section 10

Stability and Reactivity

Reactivity: Chemical Stability: Possibility of Hazardous Reaction: Conditions to Avoid: Incompatible Materials: Hazardous Decomposition Products: Stable under normal conditions. No data available None Stable under normal conditions. None in particular None

Section 11	Toxicological Informati	ion			
Toxicological Information					
	There is no toxicological data available on the mixture. Consider the individual concentrations of each component to assess toxicological effects resulting from exposure to the mixture.				
Toxicological Information on the main components of the mixture:					
	Silica Sand	a) acute toxicity	LD50 (Oral): =500 mg/kg (Rat)		
	Calcium sulfate	a) acute toxicity	LD50 (Oral): >3000 mg/kg (Rat)		

If not differently specified, the information required in the regulation and listed below must be considered NA.

a) acute toxicity b) skin corrosion/irritation c) serious eye damage/irritation d) respiratory or skin sensitization e) germ cell mutagenicity f) carcinogenicity g),reproductive toxicity h) STOT - single exposure I) STOT - repeated exposure J) aspiration hazard Substance(s) listed on the IARC Monographs: Silica Sand Group 1

Substance(s) listed as OSHA Carcinogen(s): Silica Sand Substance(s) listed as NIOSH Carcinogen(s): Silica Sand Substance(s) listed on the NTP report on Carcinogens: Silica Sand

Section 12 Ecological Information

Overview: Adopt good working practices, so that the product is not released Into the environment.

Ecotoxicity:

QTY, Chemical Name	CAS Nur	mber	Eco Toxicity
60-80%, Silica Sand	14808-60	0-7	LC 50 a) Aquatic acute toxicity carp >10000.00000 mg/L 72h
1-5 %, Calcium sulfate	7778-18	-9	LC 50 a) Aquatic acute toxicity Fish Lepomis macrochirus =2980mg/L 96h EPA LC 50 a) Aquatic acute toxicity Fish Pimephales promelas > 1970mg/L 96h EPA
Persistence and degrad			ymeric component is not expected to biodegrade.
Bioaccumulative potent	ial:	No data	
Mobility in soil:		No data	
Other Adverse Effects:		No data	

Section 13 Disposal Considerations

Disposal Methods:

Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance. Not Determined

Waste Disposal Code(s):

Section 14 Transport Information

UN number

ADR-UN number:	N/A
DOT-UN number:	N/A
IATA-UN number:	N/A
IMDG-UN number:	N/A
UN proper shipping name	
ADR-Shipping Name:	N/A
DOT Proper Shipping Name:	N/A
IATA-Technical name:	N/A
IMDG-Technical name:	N/A
Transport hazard class(es)	
ADR- Class:	N/A
DOT Hazard Class:	N/A
IATA- Class:	N/A

IMDG-Class:	N/A
Packing group	N/A
ADR Packing Group:	N/A
DOT-Packing group:	N/A
IATA-Packing group:	N/A
IMDG-Packing group:	N/A
Environmental hazards	
Marine pollutant:	No
Environmental Pollutant:	N.A.
Transport in bulk according to Annex II of MA	
	N.A.
Special Precautions	
Department of Transportation (DOT):	
DOT-Special Provision(s):	N/A
DOT Label(s):	N/A
DOT Symbol:	N/A
DOT Cargo Aircraft:	N/A
DOT Passenger Aircraft:	N/A
DOT Bulk:	N/A
DOT Non-Bulk:	N/A
Road and Rail (ADR-RID):	
ADR-Label:	N/A
ADR Hazard identification number:	N/A
ADR Tunnel Restriction Code:	N/A
Air (IATA) :	
IATA- Passenger Aircraft:	N/A
IATA- Cargo Aircraft :	N/A
IATA- Label:	N/A
IATA- Subrisk:	N/A
IATA- Erg:	N/A
IATA- Special Provisions:	N/A
Sea (IMDG):	
IMDG -Stowage Code:	N/A
IMDG -Stowage Note:	N/A
IMDG -Subrisk:	N/A
IMDG -Special Provisions:	N/A
IMDG -Page:	N/A
IMDG -Label:	N/A
IMDG -EMIS:	N/A
IMDG -MFAG:	N/A

Section 15

Regulatory Information

USA - Federal regulations

TSCA • Toxic Substances Control Act TSCA Inventory:

All the components are fisted on the TSCA inventory

TSCA listed substances:

Silica Sand	is listed in TSCA	Section 8b
Portland cement	is listed in TSCA	Section 8b
Calcium sulfate	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act Section 302 – Extremely Hazardous Substances: no substance listed

Section 304 –Hazardous substances: Section 313 – Toxic chemical list: no substance listed no substance listed

CERCLA – Comprehensive Environmental Response, Compensations, and Liability Act Substance(s) listed under CERCLA: no substance listed

CAA – Clean Air Act CAA Substances listed: no substance listed CWA – Clean Water Act CWA Substances listed: no substance listed **USA - state specific regulations** California Proposition 65 Substance(s) listed under California Proposition 65 Silica Sand listed as carcinogen Massachusetts right to know Substance(s) listed under Massachusetts Right to Know; Silica Sand Portland cement Calcium sulfate Pennsylvania Right to know Substance(s) listed under Pennsylvania Right to Know; Silica Sand Portland cement Calcium sulfate New Jersey Right to know Substance(s) listed under New Jersey Right to Know; Silica Sand Portland cement Calcium sulfate

Section 16

Other Information

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems. NFPA: HMIS III:

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

NFPA: Flammability

HEALTH*2FLAMMABILITY0PHYSICAL HAZARD0

HMIS Health:2 = MODERATEHMIS Health- Is health hazard chronic?: YesHMIS Flammability:0 = Not CombustibleHMIS Reactivity:0 = MINMALHMIS P.P.E.:Safety glasses, gloves, dust respirators

NFPA Health:	2 = MODERATE
NFPA Flammability:	0 = Not Combustible
NFPA Reactivity:	0 = MINIMAL
NFPA Special Risk:	NONE

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Texrite Multi-purpose -SDS

H318	Cause serious eye damage.
H335	May cause respiratory irritation.
H350A	May cause cancer if inhaled
H372A	Causes damage to organs through prolonged or repeated exposure if inhaled

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Texrite makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

ACGIH	-American Conference of Governmental	OSHA	-Occupational Safety and Health
	Industrial Hygienists		Administration
CAS	-Chemical Abstract Service Number	PEL	-Permissible Exposure Limit
CERCLA	A -Comprehensive Environmental Response,	ppm	-Parts per million
	Compensation, and Liability Act	RCRA	-Resource Conservation and Recovery Act
DOT	-U.S. Department of Transportation	SARA	-Superfund Amendments and
IARC	-International Agency for Research on		Reauthorization
	Cancer	TLV	-Threshold Limit Value
N/A	-Not Available	TSCA	-Toxic Substances Control Act
NTP	-National Toxicology Program	IDLH	 Immediately dangerous to life and
			health