

PRODUCT INFORMATION

tube and tile caulk

Siliconized acrylic latex caulk

TUB AND TILE CAULK is a siliconized acrylic latex caulk that forms a long-lasting, flexible, water tight seal that will resist cracking in most building materials including ceramic tile, stone, glass, wood and metals. Easily applied by the professional or homeowner, it is available in Texrite's designer grout colors in sanded or non-sanded form.

TEXTURE:

Paste - sanded or non sanded (smooth).

COLORS:

28.

PACKAGING:

10.3 oz cartridge (6 tubs per case).

AREA OF USE

TUB AND TILE CAULK is used to fill cracks or joints between adjoining surface where movement is expected such as around tubs, showers, sinks, countertops, woodwork, baseboards, doors and window frames. The maximum joint width should not exceed 1/4" (6 mm). Not for constant water exposure.

INSTALLATION:
APPLICATION

Surface shall be dry and clean, free of dust, loose paint, oil, grease and wax. Do not apply when temperature is below 50 °F (10 °C).

1. Insert cartridge into caulking gun.
2. Cut off tip to desired size.
3. Apply caulking in a smooth continuous bead and force into crack.
4. Smooth with wet finger.
5. Clean with soap and water before cure.

IMPORTANT: This product may contain high level of colorants and may stain some porous materials for example: wallpaper or walls. Masking or shielding of these areas might be necessary.

CURING

Initial cure is reached in 48 to 72 hours depending on the ambient temperature and humidity. When applied to areas exposed to moisture, wait a minimum of 7 days before exposing to intermittent water.

COVERAGE

10.3 fl. oz (310 ml) cartridge extrudes approximate linear feet:

- 1/16 x 1/16 (joint) 48 linear feet
- 1/8 x 1/8 (joint) 25 linear feet
- 3/16 x 3/16 (joint) 17 linear feet
- 1/4 x 1/4 (joint) 13 linear feet

Note: coverages shown are for estimating purposes only. Actual jobsite coverages may vary depending on joint size and application procedures.

STORAGE LIFE

Unused portions of tube maybe capped and stored in a cool, dry place and used within one year. DO NOT FREEZE

SAFETY - CAUTION: Do not take internally, avoid eye contact. Avoid skin where possible and wash exposed skin areas promptly with water.

KEEP OUT OF REACH OF CHILDREN

NOTICE TO PURCHASER: Manufacturer's liability for damages hereunder shall not exceed the purchase price of the goods used. Manufacturer warrants only that the goods will be free from defects in material. The foregoing warranty is in lieu of other warranties, expressed or implied, including those of merchantability of fitness for any purpose not expressly stated herein. In no event shall manufacturer be responsible for incidental or consequential damages arising out of or in connection with the use of this product by the user, buyer's user or any other person.