PATCH

ACRYLIC ROOF MASTIC

DESCRIPTION:

IMPAC® PATCH is an acrylic white water based plastic cement. **IMPAC® PATCH** is a crack filler that fill and repairs the surface defects.

AVAILABLE COLORS:

- White.

BENEFITS:

- Formulated with the highest technology with elastomeric acrylic resins.
- Material specially designed to be applied directly on fissures and cracks.
- **IMPAC® PATCH** is completely paintable.
- Resistant to UV rays.
- Complete impermeability and weathering resistance.
- It has excellent elongation and it is crack resistant.
- It does not require specialized tools.
- It adheres to most common construction materials.
- It protects and strengthens the surfaces where it is applied.
- Paste form, easy to apply

USES:

This material seals imperfections in concrete slabs and it can be used on a wide variety of materials so it can be used in roofs, sheet metal, parapets, skylights, chimney, pipelines, downspouts, fasteners, chamfers, etc.

Stop leaks and seal cracks

UV stable

Highly flexible

100% waterproof

Update: July 03/2026. These technical specifications replace any previous one up to this date. Visit our webpage www.impacusa.com where you can find the current version. Subjected to changes without notice.

www.impacusa.com

SAINT-GOBAIN

PRIMER

ACRYLIC ROOF PRIMER

TECHNICAL INFORMATION:

PROPERTIES	VALUE	STANDARD
Consistency	Paste	
Density	11.68 - 12.18 pounds per gal.	ASTM D-1475
Viscosity	130,000 - 150,000 cP	ASTM D-2196
Solids by weight	68 - 72%	ASTM E-70
Coverage*	Up to 205 sq. ft. / 5 gallons	ASTM D-1644
Presentation	1,2, 3 and 5 gallons	

* Performance may vary according to the roughness of the surface.

RECOMMENDATIONS:

The amount to be applied will depend on the surface and its roughness; depth and porosity. See performance table. For cracks wider than 1⁄4 inch, is recommended to review the surface in order to detect defects in the construction before continuing with the roof repair.Use soap and water for washing your skin. Clean tools with water after use them.

KEEP OUT OF REACH OF CHILDREN.

STORAGE:

Store in a clean, dry and well ventilated place avoiding direct contact of the container and/or material with sun rays or intense cold and protect it from rain. Avoid freezing temperatures.

APPLICATION:

1. CLEANING

Clean cracks and adjacent areas to be repaired from dust, oil, wax or grease; clean with a hard bristles brush to completely remove any loose materials.

2. PATCHING

This material is used directly from the container using a spatula. Patch cracks, and level irregularities that can be in the surface with **IMPAC® PATCH**, using a trowel for its application if necessary.

To correctly prepare the surface to be repaired, identify all areas of moisture infiltration and/or leaks and repair with **IMPAC® PATCH**; sealing slight cracks, and all existing 90° angles by parapets, dome bases, antenna bases, tank bases, air conditioning systems, cable entrances, ducts and more objects fitted in the slab.

Do not apply at temperaturas below 50 °F (10 °C).