PRIMER

ACRYLIC ROOF PRIMER

DESCRIPTION:

IMPAC® PRIMER is an acrylic primer sealer to be used as a part of a system with another IMPAC acrylic roofs coatings.

AVAILABLE COLORS:

- Clear.

BENEFITS:

- Eliminates porosity from surface.
- Improves waterproofing adherence and performance.
- Reduces moisture absorption.
- Environmental friendly.

USES:

IMPAC® PRIMER completely covers the porosity on different surfaces such as: concrete slabs, walls, bricks, cement boards, etc.

APPLICATION:

Apply one coat with roll or brush over all surface. Let it dry 1 -4 hours. The surface must be clean and dry.

Enhaces roof coating performance

Improves adhesion

Eliminates porosity

Blocks moisture

Update: July 03/2026. These technical specifications replace any previous one up to this date. Visit our webpage www.impacusa.com where you can find the current version. Subjected to changes without notice.

www.impacusa.com

SAINT-GOBAIN

PRIMER

ACRYLIC ROOF PRIMER

TECHNICAL INFORMATION:

PROPERTIES	VALUE	STANDARD
Consistency	Liquid	
Density	9.18 lb/gal (1.10 +/- 0.05 kg/L)	ASTM D-1475
Viscosity	2,000 - 3,000 cps	ASTM D-2196
pH	8.0 – 9.5	ASTM E-70
Solids by weight	28% - 32%	ASTM D-1644
Coverage*	450 sq. ft. / 5 gallons	
Presentation	1 and 5 gallons bucket	

* Performance may vary according to the roughness of the surface.

RECOMMENDATIONS:

Do not apply at temperatures lower than 50°F or higher than 100°F, neither in rainy days nor with a rainfall threat. Do not apply in humid surfaces. Do not apply when relative humidity is higher than 85% as in days or hours with thin fog, breeze, mist, dew, etc.
Use soap and water for washing your skin. Clean tools with water after use them.

KEEP OUT OF REACH OF CHILDREN.

STORAGE:

Store in a cool and dry place, the container must be tightly closed. Do not stow more than three buckets.