Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

* **Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC**

1 Identification

Product identifier
Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC
Application of the substance / the mixture: Roofing primer.

Details of the supplier of the safety data sheet
Manufacturer/Supplier:
POLIMEROS, ADHESIVOS Y DERIVADOS S.A. DE C.V.
JOSE ELEUTERIO GONZALEZ 900 PTE.
SANTA CATARINA, NUEVO LEON, MEXICO
CP. 66350
Phone: +52 81 50002020
Emergency telephone number: +52 81 50002138

2 Hazard(s) identification

Classification of the substance or mixture

GHS05 GHS07

Acute Toxicity - Oral 4
Skin Corrosion/Irritation 2
Serious eye damage/eye irritation 1
Sensibilization- Skin 1

Label elements

GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
Hazard pictograms

GHS05 GHS07

Signal word: Warning

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

Hazard statements

H302 Harmful if swallowed.
H315 Cause skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from flames and hot surfaces. No smoking.
P260 Do not breathe dust, fumes, gases, mists, vapors, or aerosols.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P337+P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NFPA ratings (scale 0 - 4)
Health = 3
Fire = 0
Reactivity = 0
HMIS-ratings (scale 0 - 4)
Health = 3
Fire = 0
Reactivity = 0
Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

3 Composition/information on ingredients

Chemical characterization: Mixtures
Description:

Component	CAS Registry	Concentration
Titanium dioxide	13463-67-7	3.0 - 7.0 %
Methyl-tris (2-butanonoxime)silane	22984-54-9	1.0 - 5.0 %
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	1.0 - 5.0 %
Silica, amorphous, fumed, crystalline free	112945-52-5	1.0 - 5.0 %

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures
General information:
Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.
After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact:
Remove contaminated clothes and shoes. Rinse immediately with plenty of water for at least 15 min.
In case of eczema, irritation or other skin disorders, consult a doctor.
After eye contact:
Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and lukewarm water for at least 10 minutes while pulling eyelids up and seek medical assistance. Don't let the person to rub the affected eye.
After swallowing:
Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.
Information for doctor: None
Most important symptoms and effects, both acute and delayed:
Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of any immediate medical attention and special treatment needed:
Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

*
5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents:
CO2, foam, water fog, dry chemical powder.
Unsuitable extinguishing agents:
Do not use water jet as an extinguisher, as this will spread the fire.
Special hazards arising from the substance or mixture
During fire, gases hazardous to health may be formed such as: Carbon oxides, nitrogen oxides, silicon oxides.
Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device.

*
6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources
Danger of slipping on leaked/spilled product.
Environmental precautions:
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Methods and material for containment and cleaning up:
Absorb the spillage using earth, sand or other non-combustible material and move it to a safe place. Do not absorb with sawdust or other combustible absorbents.
Dispose of the collected material according to regulations.
Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling:
Precautions for safe handling
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid breathing mist/vapors.

Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:
Store only in unopened original receptacles.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

* **Information about storage in one common storage facility:**
Store away from foodstuffs.
Further information about storage conditions:
Protect from heat and direct sunlight.
Store in dry conditions.
Store in a cool place.
Specific end use(s) No further relevant information available.

*

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see section 7.

Control parameters
Components with limit values that require monitoring at the workplace:

CAS No. Designation of material	%	Type	Value Unit
CAS: 13463-67-7 Titanium dioxide			
OSHA			
PEL			15* mg/m³ *Total dust
ACGIH			
TWA			2.5* mg/m³ *Respirable finescale particles
TWA			0.2** mg/m³ **Respirable nanoscale particles
NIOSH			
IDLH			5000 mg/m³
CAS: 112945-52-5 Silica, amorphous, fumed, crystalline free			
OSHA			
TWA			5* mg/m³ *Respirable fraction
TWA			15** mg/m³ **Total dust
TWA			0.8*** mg/m³ ***Total dust
NIOSH			
IDLH			3000 mg/m³
TWA			See Pocket Guide: 6 mg/m³

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

Exposure controls
Personal protective equipment:
General protective and hygienic measures:
The usual precautionary measures for handling chemicals should be followed.
Do not eat, drink, smoke or sniff while working.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Store protective clothing separately.
Use a moisturising skin cream after processing the product.
Protection of hands: Protective gloves
Material of gloves Butyl rubber.
Eye protection: Protective eyewear (standard EN 166)
Body protection: Protective work clothing

*

9 Physical and chemical properties

Information on basic physical and chemical properties	
General Information	
Appearance:	Liquid
Form:	Paste
Color:	According to product specification White
Odor:	Slight.
Odor threshold:	Not determined.
pH-value at 25 °C (77 °F):	6 - 11
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 212 °F (> 100 °C)
Flash point:	> 212 °F (> 100 °C) Pensky-Martens Closed Cup
Flammability:	Not applicable.
Auto igniting:	Not determined.
Decomposition temperature:	Not determined.
Ignition temperature:	Not determined.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidizing properties	Not oxidizing.
Vapor pressure at 20 °C (68 °F):	Not determined.
Density at 25 °C (77 °F):	Not available.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

Bulk density:	Not applicable.
Relative density at 25 °C (77 °F):	1.2 - 1.3
Vapor density at 25 °C (77 °F):	Not determined.
Evaporation rate	Not available.
Solubility in / Miscibility with Water:	Insoluble in water.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic at 25 °C (77 °F):	Not available.
Kinematic:	Not determined.
Solvent separation test	Not determined
Solvent content:	
Solids content:	92.0 - 98.0 %
Other information	VOC: Property has not been measured.

*
10 Stability and reactivity

Reactivity:
This product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability: Stable at recommended storage conditions
Thermal decomposition: No decomposition if used according to specifications.
Possibility of hazardous reactions: Releases small amounts of 2-butanone oxime and methanol during polymerization.
Conditions to avoid: Contact with incompatible materials.
Incompatible materials: Strong oxidizing agents, strong acids, strong bases.
Hazardous decomposition products: Carbon monoxide, carbon dioxide, nitrogen oxides and silicone oxides.

*
11 Toxicological information

Information on toxicological effects
Acute toxicity: Not expected to be acutely toxic.
LD/LC50 values that are relevant for classification:

Components	Type	Value	Species
CAS: 22984-54-9 Methyl-tris (2-butanonoxime)silane			
Oral	LD50	2463 mg/kg (Rat)	
CAS: 1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine			
Dermal	LD50	> 2000 mg/kg (Rat)	
Oral	LD50	2413 mg/kg (Rat)	
CAS: 13463-67-7 Titanium dioxide			
Oral	LD50	> 5000 mg/kg (Rat)	

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

Primary irritant effect:
On the skin: Causes skin irritation. May cause an allergic skin reaction.
On the eye: Causes serious eye damage.
Sensitization: This product may cause skin sensitization.

Additional toxicological information:
Germ cell mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Reproductive toxicity: This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure: Not classified.
Specific target organ toxicity - repeated exposure: Not classified.
Chronic effects: Prolonged inhalation may be harmful.

Carcinogenic categories

IARC (International Agency for Research on Cancer)
CAS 112945-52-5 Silica, amorphous, fumed, crystalline free: 3, not classifiable as to carcinogenicity to humans. CAS 13463-67-7 Titanium dioxide: 2B, possibly carcinogenic to humans.
NTP (National Toxicology Program)
None of the ingredients is listed.
OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

Toxicity
Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Type of test	Effective concentration	Method	Assessment
CAS: 1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine			
EC50/48h	90 mg/l (Crustacea)		
EC50/72h	9.8 mg/l (Algae)		
LC50/96h	> 100 mg/l (Fish)		
CAS: 13463-67-7 Titanium dioxide			
EC50/48h	> 100 mg/l (Crustacea)		
LL50/96h	> 100 mg/l (Fish)		

Persistence and degradability: No further relevant information available.
Behavior in environmental systems
Bioaccumulative potential
Partition coefficient n-octanol / water (log Kow):
No data available.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

Mobility in soil: Not available.
Ecotoxical effects: Not available.

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.
Results of PBT and vPvB assessment PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Waste treatment methods
Waste disposal key:
The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsable for waste disposal.

Waste disposal key:
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Uncleaned packagings:
Recommendation:
Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14 Transport information

UN-Number **DOT, ADR, IMDG, IATA**	Not aplicable. Not aplicable.
UN proper shipping name	Not aplicable.
Transport hazard class(es)	Not aplicable.
Packing group	Nto aplicable.
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not isted.
CERCLA Hazardous Substance List (40 CFR 302.4)
Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance
Not listed.
SARA 311/312 Hazardous chemical
Yes

Classified hazard categories
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization

SARA 313 (TRI reporting): Not regulated.

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SDWA): Not regulated.

US State Regulations

US. Massachusetts RTK - Substance List
CAS 112945-52-5 Silica, amorphous, fumed, crystalline free
CAS 13463-67-7 Titanium dioxide

US. New Jersey Worker and Community Right-to-Know Act
CAS 13463-67-7 Titanium dioxide

US. Pennsylvania Worker and Community Right-to-Know Law
CAS 112945-52-5 Silica, amorphous, fumed, crystalline free
CAS 13463-67-7 Titanium dioxide

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

US. Rhode Island RTK
CAS 112945-52-5 Silica, amorphous, fumed, crystalline free
CAS 13463-67-7 Titanium dioxide

US. California Proposition 65
WARNING: This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance
CAS 13463-67-7 Titanium dioxide; Listed: September 2, 2011.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))
CAS 13463-67-7 Titanium dioxide

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical No Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
Hazard pictograms

GHS05 GHS07

Signal word Warning
Hazard statements

H302 Harmful if swallowed.
H315 Cause skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from flames and hot surfaces. No smoking.
P260 Do not breathe dust, fumes, gases, mists, vapors, or aerosols.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P337+P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/04/2026 Reviewed on 10/04/2026

Trade name: IMPAC TOP ROOF PRO SILICONE MASTIC

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: R&D
Contact:
José Urquidi
+52 81 5000 2120
jose.urquidi@impac.com.mx
Date of preparation / last revision 10/04/2026/ -
Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Toxicity - Oral 4: Acute toxicity – Category 4
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Skin 1: Skin sensitisation – Category 1
*** Data compared to the previous version altered.**
According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous